

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

H₂O Flow



Purge Flow



ZrCl₄ Flow



FIG. 1

Precursor Flow



Purge Flow



Oxidizer Flow



FIG. 2

80




FIG-3




FIG.4

Showerhead holes	220
Hole length	6.1 mm
Hole Diameter	0.97 mm
Line I.D.	10.7 mm
Line Lenth	560 mm
Chamber Pressure	1.0 mT
Plenum Pressure	2.4 mT
Valve Inlet Pressure	21.6 mT
Flow Controller Exit Press.	50.0 mT
Flow Controller Inlet Press.	>100 mT
Vapor Pressure Requirement	>300 mT
HTB Temperature Requirement	< 41 °C

Figure 5. Backpressure model results for a 1 sccm flow of HTB.




Figure 6. Vapor pressure curve for Hafnium tert-Butoxide (HBT), showing a vapor pressure of 1 torr @ 60 °C and 0.3 torr @ 41 °C. (Schumacher data sheet)




Figure 7. Vapor pressure curve for HfCl₄, showing a vapor pressure of 1 torr @ 172 °C and 0.3 torr @ 152 °C. (Schumacher data sheet)




FIGURE 8a




FIGURE 86




FIGURE 9




FIGURE 10




FIGURE 11